

State of Georgia 2016 Mass Transit Solicitation

99999-SPD-SPD0000138

APTA Form CER 10: Vehicle Technical Information

NOTE: This is a sample form. The Agency should customize it to comply with its proposed requirements.

This form must be completed and included in the Technical Proposal.

GENERAL COACH DATA SHEET

[insert bus type]

Bus manufacturer:

EIDorado National (California), Inc.

Bus model:

E-Z Rider II 35'

Understructure manufacturer:

EIDorado National (California), Inc.

Model number:

E-Z Rider II 35'

Basic Body Construction

Type:

Monocoque Type Space Frame

Tubing or frame member thickness and dimensions

Overstructure

Various sizes of steel tubing

Understructure

Various sizes of steel tubing

Skin thickness and material

Roof

.063 aluminum

Sidewall

.080 aluminum

Skirt panel

.125 fiberglass composite

Front end

.125 fiberglass

Rear end

.125 fiberglass

Dimensions

Overall length

Over bumpers

36

ft

4

in.

Over body

35

ft

6

in.

Overall width

Over body excluding mirrors

8

ft

6

in.

Over body including mirrors—driving position

10

ft

1

in.

Over tires front axles

8

ft

5

in.

Over tires center axle

N/A

ft

N/a

in.

Over tires rear axles

8

ft

5

in.

Overall height (maximum)


10	ft	5	in.
9	ft	10.5	in.

Overall height (main roof line)

Angle of approach	8.7	deg
Breakover angle	8.9	deg
Breakover angle (rear)	N/A	deg
Angle of departure	8.7	deg

Doorway Dimensions	Front		Rear	
Width between door posts	40	in.	42	in.
Door width between panels	35	in.	37	in.
Clear door width	32	in.	34	in.
Doorway height	79.5	in.	79.5	in.
Knuckle clearance	1.5	in.	1.5	in.

Step height from ground measured at center of doorway



	Front doorway, empty		Ramp angle		Rear Doorway, empty	
Kneeled	a.	11 in.	R1	14 deg	a.	11 in.
Unkneeled	b.	14 in.	R2	14 deg	b.	14 in.

Interior head room (center of aisle)

Front axle location	95	in.
Center axle location	N/A	in.
Rear axle location	79	in.

Aisle width between transverse seats 22 in. Dependent upon agency selected floorplan

Floor height above ground (centerline of bus)

At front door	14	in.
At front axle	17.38	in.
At drive axle	33.38	in.

At rear door in.

Minimum ground clearance (between bus and ground, with bus unkneeled)

Excluding axles in.

Including axles in.

Horizontal turning envelope (see diagram below)

Outside body turning radius, TR0 (including bumper)

36	ft	6	in.
----	----	---	-----

Front inner corner radius, TR1

31	ft	3	in.
----	----	---	-----

Front wheel inner turning radius, TR2


25	ft	1	in.
----	----	---	-----

Front wheel outer turning radius, TR3

31	ft	1	in.
----	----	---	-----

Inside Body Turning Radius innermost point, TR4 (including bumper)

16	ft	10.5	in.
----	----	------	-----



Wheel base

Front in.

Rear in.

Overhang, centerline of axle over bumper

Front in.

Rear in.

Floor

Interior length

20	ft	11	in.
----	----	----	-----

Interior width (excluding coving)

7	ft	11	in.
---	----	----	-----

Total standee area (approximately)

	ft ²
--	-----------------

Minimum distance between wheelhouses: Front

34.5	in.
------	-----

Rear

34	in.
----	-----

Center

N/A	in.
-----	-----

Maximum interior floor slope (from horizontal)

4	deg
---	-----

Passenger capacity provided

Total maximum seating	30	
Standee capacity	15	
Minimum hip to knee room	27	in.
Minimum foot room	14	in.

Weight

	No. of people	Front axle			Center axle			Rear axle			Total bus
		Left	Right	Total	Left	Right	Total	Left	Right	Total	
Empty bus, full fuel and farebox	N/A	3609	3331	6940	N/A	N/A	N/A	10030	9260	19290	26230
Fully seated, full fuel and farebox	30 + Driver	4209	4148	8357	N/A	N/A	N/A	11946	10577	22523	30880
Fully loaded standee and fully seated, full fuel and farebox	30 + 15 + Driver	5160	5099	10259	N/A	N/A	N/A	12120	10751	22871	33130
Crush load (1.5x fully loaded)					N/A	N/A	N/A				
GVWR				11250	N/A	N/A	N/A			23000	34000
GAWR				12000	N/A	N/A	N/A			23000	

Engine, main

Manufacturer	Cummins Engine Co.			
Type and weight rating	4 cycle in-line turbocharged air cooled			
Model number	ISL 280 HHD			
Bore		4.49 in.		
Stroke		5.69 in.		
Displacement		543 cubic in.		
Compression ratio	16.6:1			
Injector type and size	Bosch XP1			
Net SAE horsepower		280hp at	2200	RPM
Net SAE torque		900lb/ at ft	1300	RPM
Crankcase oil capacity				
New engine, dry		7.3 gal		
New engine, wet		7 gal		
Turbocharger make and model	Holset			
Maximum speed, no load		2400 RPM		
Maximum speed, full load		2200 RPM		
Speed at idle		700 RPM		
Speed at fast idle		1000 RPM		

Engine information/graphs to be attached with this form:

Engine speed vs. road speed
Torque vs. engine speed
Horsepower vs. engine speed
Fuel consumption vs. engine speed
Vehicle speed vs. time (both loaded and unloaded)
Vehicle speed vs. grade (both loaded and unloaded)
Acceleration vs. time
Change of acceleration vs. time

Hybrid drive or transmission

Manufacturer	Allison B400R Transmission			
Type	Automatic			
Speeds	5			
Gear ratios	Forward:	3.49,1.86, 1.41,1.0,.075	Reverse:	5.03
Shift speeds				
1st–2nd	10	mph		
2nd–3rd	21	mph		
3rd–4th	30	mph		
4th–5th (if applicable)	40	mph		
5th–6th (if applicable)	N/A	mph		
Fuel capacity (including heat exchanger and filters)	28 quarts			

Voltage regulator

Manufacturer	Delco
Model	50VR

Voltage equalizer

Manufacturer	Vanner
Model	70-60

Alternator

Manufacturer	CE Niehoff		
Type	28 Volt Negative Ground		
Model	C803D		
Output at idle		320 amps	
Output at maximum speed		525 amps	
Maximum warranted speed		8000 rpm	
Speed at idle (approximately)		2000 – 2200 rpm	
Drive type	Belt Driven		

Starter motor

Manufacturer	Denso
--------------	-------

Type	Electric
Model	428000-0060

Air compressor

Manufacturer	Wabco 30.4		
Type	Twin Cylinder		
Rated capacity	30.4	CFM	
Capacity at idle (approximately)	15.9	CFMs	
Capacity at maximum speed (engine)	2400	CFM	
Maximum warranted speed	2200	rpm	
Speed idle	750	rpm	
Drive type	Direct		
Governor:			
Cut-in pressure	105	psi	
Cut-out pressure	125	psi	

Axles

First

Manufacturer	Arvin Meritor		
Type	I-Beam		
Model number	MFS 13		
Gross axle weight rating		12000 lbs	
Axle load		11000 lbs	

Second

Manufacturer	N/A		
Type			
Model number			
Gross axle weight rating		lbs	
Axle load		lbs	

Third (REAR)

Manufacturer	Arvin Meritor		
Type	Full Floating		
Model number	RS23		
Gross axle weight rating		23000 lbs	
Axle load		23000 lbs	
Axle ratio	5.38		

Suspension system

Manufacturer	EIDorado National		
Type:	Front:	Air Ride – Trailing arm taper leaf	
	Rear:	Air Ride – Trailing arm taper leaf	
	Third:	N/A	

Springs:	Front:	(2) Rolling Lobe Air Springs per axle
	Rear:	(2) Rolling Lobe Air Springs per axle
	Third:	N/A

Joint N/A

Manufacturer	N/A
Type	N/A
Model number	N/A

Wheels and tires

Wheels

Make	Accuride - Hub Piloted
Size	22.5" x 7.5"
Capacity	6610
Material	Powder Coated Steel

Tires

Manufacturer	Customer Supplied
Type	
Size	275/70R22.5
Load range/air pressure	130 psi

Steering, power

Pump

Manufacturer and model number	Eaton Series 26
Type	Gear Pump
Relief pressure	1915 psi

Booster/gear box

Manufacturer and model number	Sheppard – M100
Type	Hydraulic
Ratio	18.9:1

Power steering fluid capacity	2 gal
Maximum effort at steering wheel	7-10 lbs (unloaded stationary coach on dry asphalt pavement)
Steering wheel diameter	20 in.

Brakes

Make of fundamental brake system	Bendix/Wabco		
Brake chambers vendor size and part number:	Front:	20" MGM	
	Rear:	3030 MGM	
	Third:	N/A	
Brake operation effort	20 lbs – 7" away from heel point		

Slack adjuster's vendor's type and part numbers N/A

First:	Right:	Haldex – Automatic A5 3275G 1099
	Left:	Haldex – Automatic A5 3275G 1098
Second:	Right:	Haldex – Automatic A28 3275S 1059
	Left:	Haldex – Automatic A28 3275S 1059
Third:	Right:	N/A
	Left:	N/A
Length:	First take-up:	5.50
	Second take-up:	6.50
	Third take-up:	N/A

Brake drums/discs

Front:	Manufacturer	Meritor	
	Part number	85123681002	
	Diameter	15	in.
Rear:	Manufacturer	Meritor	
	Part number	85123207002	
	Diameter	16	in.
Third:	Manufacturer	N/A	
	Part number	N/A	
	Diameter	N/A	in.

Brake lining manufacturer	Abex
Type	Q Plus

Brake lining identification

Front:	Forward	LM – MA212
	Reverse	LM – MA212
Rear:	Forward	R301/LM – ABB931-162
	Reverse	R301/LM – ABB931-162
Third:	Forward	N/A
	Reverse	N/A

Brake linings per shoe

Front:	2
Rear:	2
Third	N/A

Brake lining widths

Front:	6	in.
Rear:	17	in.
Third	N/A	in.

Brake lining lengths

Front:	15	in.
Rear:	16.5	in.
Third	N/A	in.

Brake lining thickness in.

Brake lining per axle

Front:	384	sq. in.
Rear:	462	sq. in.
Third	N/A	sq. in.

Cooling system**Radiator/charge air cooler**

Manufacturer	Modine				
Type	Over under module design				
Model number	E-Fan Gen 2				
Number of tubes	228/15				
Tubes outer diameter	1	in./	4.25	in.	
Fins per inch	10	fins			
Fin thickness	Aluminum	in.			
Total cooling and heating system capacity	20	gal			
Radiator fan speed control	Digital type				
Surge tank capacity	16	quarts			
Engine thermostat temperature setting: Initial opening (fully closed)	185	°F			
Fully open	195	°F			
Overheat alarm temperature sending unit setting	225	°F			
Shutdown temperature setting	230	°F			

Air reservoir capacity

Supply reservoir	1224	in. ³
Primary reservoir	2495	in. ³
Secondary reservoir	2495	in. ³
Packing reservoir	2429	in. ³
Accessory reservoir	2429	in. ³
Other reservoir type	N/A	in. ³

Heating, ventilation and air conditioning equipment

Heating system capacity	115000	BTU/hr
Air conditioning capacity	115000	BTU
Ventilating capacity	3000	CFM

Compressor

Manufacturer	Thermo King			
Model	X430			
Number of cylinders		4		
Drive ratio		1:1		
Maximum warranted speed		2600		rpm
Operating speed		2200		rpm (recommended)
Weight		110		lbs
Oil capacity	Dry	8.9 pints	gal	
	Wet	N/A	gal	
Refrigerant:	Type	R407C	17	lbs

Condenser

Manufacturer	Thermo King		
Model	Athenia AM II		
Number of fins/in.	11		
Outer diameter of tube	0.375	in.	
Fin thickness	0.016	in.	

Condenser fan

Manufacturer	EBM		
Model	W3G300 ECDC		
Fan diameter	12	in.	
Speed maximum	3300	rpm	
Flow rate (maximum)	5500	CFM	

Receiver

Manufacturer	Thermo King		
Model	Horizontal Type		
Capacity	125	lbs	

Condenser fan drive motors

Manufacturer	EBM		
Model	W3G300		
Type	ECDC		
Horsepower	0.30	hp	
Operating speed	3300	rpm	

Evaporator fan drive motors

Manufacturer	EBM		
Model	K3G097		
Type	ECDC		

Horsepower	0.30	hp
Operating speed	4400	rpm

Evaporator(s)

Manufacturer	Thermo King	
Model	Athenia AM II	
Number of rows	4	
Number of fins/in.	10	
Outer diameter of tube	0.375	in.
Fin thickness	0.016	in.
Number of evaporators	6 circuits	Per cell

Expansion valve

Manufacturer	Danfoss
Model	Tube

Filter-drier

Manufacturer	Thermo King
Model	Various – disposable in-line type

Heater cores

Manufacturer	Thermo King	
Model	Athenia AM II	
Capacity	115000	Btu/hr
Number of rows	2	
Number of fins/in.	8	
Outer diameter of tube	0.375	in.
Fin thickness	0.008	in.
Number of heater cores	4 circuits	Per coil

Floor heater blowers - Optional

Front	
Rear	

Controls

Manufacturer	Thermo King
Model	Intelligaire III

Driver's heater

Manufacturer	Mobility Climate Controls	
Model	13-14114	
Capacity	60000	Btu/hr

Ventilation system

Type	Thermo King/Mobility Climate Controls
------	---------------------------------------

Coolant heater - Optional

Make		
Model		
Capacity		Btu

Interior lighting

Manufacturer	I/O Controls	
Type	LED	
Number of fixtures	9	
Size of fixtures	72"	
Power pack	Driver Module	

Doors**Front**

Manufacturer of operating equipment	Vapor
Type of door	Slide/Glide
Type of operating equipment	Electro-pneumatic

Rear

Manufacturer of operating equipment	Vapor
Type of door	Slide/Glide
Type of operating equipment	Electro-pneumatic

Passenger windows**Front**

Manufacturer	Dura		
Model	Traditional Frame T3		
Type	Full Height Slider		
Number:	Side	12	
	Rear	N/A	
Sizes:	43.00 x 46.50		34.56 x 46.50
	43.00 x 46.38		34.56 x 50.00
Glazing:	Type	Laminated Glass	
	Thickness	1/4"	
	Color of tint	Gray	
	Light transmission	28%	

Mirrors

	Size	Type	Manufacturer	Part no.	Model no.
--	------	------	--------------	----------	-----------

Right side exterior	15x8	Combo	SafeFleet	CS-23-D913HRFHRCX-OTS	CS-23-D913HRFHRCX-OTS
Left side exterior	15x8	Combo	SafeFleet	RS-7-U13HRFHRCX-OTS	RS-7-U13HRFHRCX-OTS
Center rearview	15x4	Convex	Lucerex	23.987.00	23.987.00
Front entrance area	N/A				
Upper-right corner	6"	Convex	Rosco	BAS3001	
Rear exit area	12"	Convex	Rosco	362R	

Seats

Passenger

Manufacturer	Freedman
Model	Featherweight
Type	Mid Hi

Operator

Manufacturer	Recaro
Model and part number	Ergo Metro AM80
Type	Air Suspension

Paint

Manufacturer	Akzo Nobel, Sikkens
Type	Autocoat BT

Wheelchair ramp equipment

Manufacturer	Lift-U		
Model number	LU18		
Capacity	950	lbs	
Width of platform	32	in.	
Length of platform	48	in.	
System fluid capacity	N/A	quarts	
Type of fluid used	N/A		
Operating hydraulic pressure	N/A	Psi	NOTE: Electrically deployed
Hydraulic cylinders:	Size	N/A	
	Number	N/A	

Wheelchair securement equipment

Manufacturer	Q'Straint
Model number	QRT 8100-A1 Deluxe

Destination signs

Manufacturer	Twin Vision / Transign
Type	SMART Series 3 100% Amber LED / Mechanical

Character length

Front destination		in. Programmable
Front route	2.25	in. Transign
Curbside destination		in. Programmable
Rear route	18	in. Programmable

Character height

Front destination	8.0	in. Programmable
Front route	4.25	in. Transign
Curbside destination	4.3	in. Programmable
Rear route	6.1	in. Programmable

Number of characters

Front destination		Programmable
Front route	4	Transign
Curbside destination		Programmable
Rear route		Programmable

Message width

Front destination		in. Programmable
Front route	9	in.
Curbside destination		in. Programmable
Rear route		in. Programmable

Electrical**Multiplex system**

Manufacturer	I/O Controls
Model number	Dinex G3

Batteries

Manufacturer	Deka
Model number	8D, Side Post
Type	1300 CCA each

Communication system**GPS**

Manufacturer	N/A
Model number	N/A

PA system

	Manufacturer	Model number	Number
Amplifier	REI	700890	
Microphone	REI	480037BK	

Internal speakers	REI	603B/6LP	8
External speaker	REI	220010	1

Energy storage (hybrid drive) - Optional

Type			
Number of cells		V	
Battery pack voltage		V	
Weight		lbs	

Security camera system – Optional

Manufacturer	Prewire only provided in base		
Model number			
Number of cameras			
Storage capacity			

Bike racks - Optional

Manufacturer			
Model number			

Fire detection system

Manufacturer	Amerex		
Model number	V25		
Fire detectors	Fixed Temperature		
Type (thermal or optical)	Thermal		
Number of detectors	4		

Automatic voice annunciator system – Not in base

Manufacturer			
Model and part number			

Annunciator LED sign – Not in base

Number of signs		
Housing dimensions		
Character length		in.
Character height		in.
Character width		in.

GPS antenna

Manufacturer	Per customer request		
Model and part number			

Automatic passenger counter – Not in base

Manufacturer	
Model and part number	a.
	b.
	c.
Sensor type	

Real-time bus arrival prediction system – Not in base

	Manufacturer	Model number
Router		
Cellular modem		
Charge protection		

Electronic tire pressure monitoring system – Not in base

Manufacturer	
Model number	

Electronic brake stroke/wear indicator system - Optional

Manufacturer	
Model number	

NOTE: All information above is accurate to the timeframe upon submission. The Agency reserves the right to update above data if changes occur, upon consultation with the customer.

